

# NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI014258.01  
**DATE:** 11/12/2018  
**CERTIFICATION PROGRAM:** Structural  
**COMPANY:** American Openings  
**CODE:** 1348-1

To verify that the "Notice of Product Certification" is valid, please visit [www.NAMICertification.com](http://www.NAMICertification.com) to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>American Openings, Inc.</b> 6885 E. Southpointe Road Tucson, AZ 85734	<b>Series "CA 400/420"</b>  <b>Vinyl Out-Swing Casement</b>  Configuration: OX Glazing: Insulating Glass (Annealed)  Frame: W-1511mm(59.5") H-1511mm(59.5") Panel: W-716mm(28.19") H-1448mm(57") DLO: W-633mm(24.94") H-1365mm(53.75")

SPECIFICATION	PRODUCT RATING
AAMA/WDMA/CSA 101/L.S.2/A440-17 AAMA/WDMA/CSA 101/L.S.2/A440-11 AAMA/WDMA/CSA 101/L.S.2/A440-08 AAMA/WDMA/CSA 101/L.S.2/A440-05 CSA A440S1-09	Class LC-PG30 1524 x 1524* (60 x 60)*-C C-LC-30 1524 x 1524* (60 x 60)* Design Pressure: ±1440 Pa (30 psf) Positive Design Pressure: 1680 Pa (35 psf) Negative Design Pressure: 1440 Pa (30 psf) Water Penetration Resistance Pressure: 440 Pa (9.19 psf) Canadian Air Infiltration/Exfiltration Level: A3

**Product Tested By:** Intertek, PLC  
**Report No:** H9814.02-501-47  
**Expiration Date:** January 31, 2022

A handwritten signature in dark ink, appearing to be 'M.D.' or similar initials.

Administrator's Signature: \_\_\_\_\_

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway  
 Hayes, VA 23072  
 Tel: (804) 684-5124  
 Fax: (804) 684-5122